

# Address Risk API 4.1 Source Development Guide

### **Document History**

Date	Changes
8 September 2024	Update: Included disclaimer for usage of Identity Risk Model
30 December 2024	<b>Update:</b> Branding update to remove Ekata and reflect Mastercard. Broke up "zip+4" into "postal_code" and "zip4" response signals with definitions. Updated Response Sample with US address to reflect what customers would see when querying US data.

#### **Table of Contents**

Document History	
Source Development Guide Overview	
Address Risk API 4.1	
Query Parameters	
Responses	5
Request	9
Request Samples: cURL	9
Response Samples	9
Error Handling	10
How To Respond to Error Codes	11



## **Source Development Guide Overview**

To establish best practices of API requests, this document should be used with the associated Integration Guide. The Integration Guide provides additional accepted formats for the following:

- Street line 1
- Street line 2
- City
- Postal code
- State code
- Country code

The Address Risk API validates global addresses and provides fraud risk signals in fractions of a second.



## Address Risk API 4.1

## **Query Parameters**

All parameters are string unless noted.

Query Parameters	Description
transaction_id required	<b>Desc:</b> The identifier associated with the event
street_line_1	Example: street_line_1=100 Syrws St  Desc: The first line of the street part in the primary structured address.  Limit: Cannot exceed 1000 characters.
street_line_2	Example: street_line_2=Ste 1  Desc: The second line of the street part in the structured.  Limit: Cannot exceed 1000 characters.
city	Example city=London  Desc: The name of the city in the structured address.  Limit: Cannot exceed 500 characters.
postal_code	Example: postal_code=N7 8XG  Desc: The postal code of the structured address.  Limit: Cannot exceed 100 characters.
state_code	Example: state_code=JS  Desc: The state code of the structured address.  Limit: Cannot exceed 100 characters.
country_code	Example: country_code=GB  Desc: The ISO-3166 alpha-2 country code associated with the phone number.  Note: See the Integration Guide for additional information.



# Responses

[200]

Response Schema: application/json

Signals	Description
id	string or null
	The unique ID of the address.
validity_level	string or null
	Enum: "valid_to_house_number" "missing_address" "invalid" "valid_to_street" "valid_to_country" "valid_to_city" "valid_to_house_number_missing_apt"
	The most granular level to which the address could be validated. Ex. If the address was only valid to the city level (but not to the house level), it would return "valid_to_city".
	• missing_address - An input address was not provided.
	• <b>invalid</b> – The input address is not valid.
	• <b>valid</b> – The input address is valid.
	<ul> <li>valid_to_country - The input address could only be validated to the country level. This means the country of the input address is valid, but the other elements of the input address were unable to be confirmed as valid or invalid.</li> </ul>
	<ul> <li>valid_to_city – The input address was validated to the city level. This means the country, state, city, and postal code of the input address are valid, but the street, house number, and subpremise of the input address were unable to be confirmed as valid or invalid.</li> </ul>
	<ul> <li>valid_to_street - The input address was validated to the street level. This means the country, state, city, postal code, and street of the input address are valid, but the house number and subpremise of the input address were unable to be confirmed as valid or invalid.</li> </ul>
	<ul> <li>valid_to_house_number – The input address was validated to the street and house number level. This means the country, state, city, postal code, street, and house number of the input address are valid, but the subpremise of the input address was unable to be confirmed as valid or invalid.</li> </ul>
	<ul> <li>valid_to_house_number_missing_apt – The input     address was validated to the street and house number     level. This means the country, state, city, postal code,     street, and house number of the input address are valid,     but the subpremise of the input address was missing and     thus unable to be confirmed as valid or invalid.</li> </ul>



Signals	Description	
street_line_1	string or null	
	The first line of the street part in the structured address.	
street_line_2	string or null	
	The second line of the street part in the structured address.	
city	string or null	
	The name of the city in the structured address.	
postal_code	string or null	
	The postal code of the structured address.	
zip4	string or null	
	Additional four digits (aka "plus-four codes") used to specify a more specific mailing location. (United States only)	
state_code	string or null	
	The state code of the structured address.	
country_code	string or null	
	The unique ID of the address.	
lat_long	Object (LatLong)	
	The coordinates of the geographical location of the address.	
latitude	number or null	
	The latitude coordinate of the location.	
longitude	number or null	
	The longitude coordinate of the location.	
accuracy	string or null	
	Enum: "Neighborhood" "Country" "PostalCode" "Street" "City" "State" "RoofTop"	
	The accuracy of the geographical location.	
last_seen_days	integer <int64> or null</int64>	
	Count of days since the address was last observed in Ekata's Identity Network. If the address has not been observed before, last_seen_days will be 0.	



Signals	Description
first_seen_days	integer <int64> or null</int64>
	Count of days since the address was first observed in Ekata's Identity Network. If the address has not been observed before, first_seen_days will be 0.
popularity	integer <int64> or null</int64>
	Greatest number of observed merchants an address has transacted with over the past 90 days; calculated from Ekata's Identity Network. If the address has not been observed in the network in the past 90 days, popularity will be 0.
velocity	integer <int64> or null</int64>
	Count of times an address has been observed in Ekata's Identity Network over the past 90 days. If the address has not been observed in the network in the past 90 days, velocity will be 0.
volatility	integer <int64> or null</int64>
	The greatest number of observed pairings with an address in Ekata's Identity Network over the past 90 days. If the address has not been observed in the network in the past 90 days, volatility will be 0.
input completeness	string or null
	Enum: "Empty" "Partial" "Missing" "Complete"
	Returns an indicator of input completeness for the address entity.
address_risk_score	Number or null [ 0 1 ] <double> ^0\.[0-9]{1,3}/1\.0</double>
	Score between 0 and 1 rounded to three decimal places. Returns a holistic risk assessment of an address where a higher score indicates a riskier transaction. Is null when the address could not be validated to at least street level or does not return network features.
	<b>Note:</b> address_risk_score is returned in Address Risk 4.1 and not returned in version 4.0.
error	PartialError (object) or InternationalPhoneDisabledErrorSearchV30 (object) nullable



Signals	Description
Warnings	array of strings
	Items Enum
	Address: "Both parsed and postal address parameters provided, postal address parameters ignored."
	Address: "Country Validated"
	Address: "Historical resident matched"
	Address: "Input postal code was corrected"
	Address: "Input postal code was corrected. Potential impact to AVS code."
	Address: "Input state corrected"
	Address: "Invalid house/building number"
	Address: "Missing country_code"
	Address: "Missing Input"
	Address: "Partial Address"
	Address: "Resident not found at address"
	Address: "State, Country Validated"
	Address: "Street, Postcode, City, Country Validated. Premise not validated"



**Get** /4.1/location\_intel

## Request Samples: cURL

```
curl --get -H "Authorization: Bearer <API_KEY>"
'https://api.ekata.com/4.1/location_intel' \
--data-urlencode 'street_line_1= 1301 5th Ave Ste 1600' \
--data-urlencode 'street_line_2=' \
--data-urlencode 'city= Seattle' \
--data-urlencode 'state_code= WA' \
--data-urlencode 'postal_code= 98101' \
--data-urlencode 'country_code= US'
```

#### **Response Samples**

```
"id": "Location.ab4a96f3-fe4e-3532-868b-8f8509e5700c",
"validity_level": "valid",
"street_line_1": "1301 5th Ave Ste 1600",
"street_line_2": null,
"city": "Seattle",
"postal_code": "98101",
"zip4": "2625",
"state_code": "Seattle",
"country_code": "US",
"lat_long": {
      "latitude": 47.60869,
      "longitude": -122.33375,
      "accuracy": "RoofTop"
},
"last_seen_days": 8,
"first_seen_days": 23,
"popularity": 34,
"velocity": 234,
"volatility": 24,
"input_completeness": "Complete",
"address_risk_score": 0.388,
"error": null,
"warnings": "Input postal code was corrected"
```



## **Error Handling**

Ekata uses conventional HTTP response codes to indicate success or failure of a request. Codes in the 2xx range indicate a successful response. Codes in the 4xx range indicate an error that resulted from the API request. Codes in the 5xx range indicate an error within Ekata's system. Contact <a href="mailto:support@ekata.com">support@ekata.com</a> for help on errors that can't be resolved.

HTTP Code	Error Name	Error Message(s)	Likely Cause
400 Bad Request	MissingInput	account_signup_id_required account_signup_time_required phone_or_email_address_required	API request is missing one or both required inputs.
401 Unauthorized	AuthError	invalid-auth-token	API key is not provided in the API request.
402 Payment Required	QuotaExceededErr or	quota-exceeded	API key has exceeded its lifetime quota of requests.
403 Forbidden	AuthError	action-unauthorized	Configuration issue on Ekata's end or invalid input sent.
403 Forbidden	AuthError	invalid-auth-token	API key provided is invalid.
403 Forbidden	AuthError	ip-blocked	API request is from an IP address that isn't on the permitted IPs list.
403 Forbidden	AuthError	token-archived	API key has been archived.
403 Forbidden	AuthError	token-disabled	API key is not valid yet.
403 Forbidden	AuthError	token-expired	API key has expired.
404 Not Found	InvalidResourceURI	Invalid resource URI	API request has been made to an invalid URI/endpoint
429 Too Many Requests	-	-	API key has exceeded its rate limit.
500 Internal Server Error	InternalError	internal-error	Internal error on Ekata's end.



## **How To Respond to Error Codes**

- 4xx error code is returned, review and correct the input.
- 429 error code is returned, the call will *not* automatically retry the query. Retry requests once the rate of 429 responses has returned to normal.

For Account Opening API, it is recommended to configure timeouts at 1000ms.



#### **Disclaimers**

This model is designed to be an informational tool only. This model is provided as a rough estimate of authentication-based risk decisioning performance. The analysis performed by this model is a series of general estimates which are based upon the underlying information and assumptions now available. That information may change over time, and the analysis would need to be updated to reflect those changes for the analysis to be useful. The assumptions regarding authorization rates are hypothetical and there can be no guarantee that they will be achieved. Actual results may vary substantially from the figures shown. Mastercard accepts no responsibility for any losses arising from any use of or reliance upon any calculations or conclusions reached using this Model.

MASTERCARD MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING (A) THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NON-INFRINGEMENT; (B) RELATING TO THE PERFORMANCE OF SMART AUTHENTICATION OR USE OF RISK INFORMATION; (C) THAT USE OF SMART AUTHENTICATION OR RISK INFORMATION SHALL BE UNINTERRUPTED OR ERROR-FREE; OR (D) CONCERNING THE ACCURACY, QUALITY, RELIABILITY, SUITABILITY, OR EFFECTIVENESS OF THE RISK INFORMATION OR ANY OTHER DATA, RESULTS, CONTENT, OR OTHER INFORMATION OBTAINED OR GENERATED BY COMPANY THROUGH ITS USE OF SMART AUTHENTICATION OR ANY RISK INFORMATION. SMART AUTHENTICATION, RISK INFORMATION, AND OTHER MASTERCARD IP IS PROVIDED "AS IS," WITH ALL FAULTS, KNOWN AND UNKNOWN. THE COMPANY ASSUMES THE ENTIRE RISK ARISING OUT OF ITS USE OF SMART AUTHENTICATION AND ITS USE OF THE RISK INFORMATION UNDER ALL APPLICABLE LAWS, INCLUDING THOSE RELATING TO PRIVACY AND DATA PROTECTION, BANKING, CREDIT, AND ANTI-DISCRIMINATION.

